

EcoPrint

HEAT TRANSFER FLOCK FILM



EcoPrint offers a great alternative to flex materials. A heat applied flock-film suitable for printing with eco-solvent, solvent and water-based pigmented inks, EcoPrint makes processing simple, producing a soft to the touch matte finish.

COMPOSITION

Base	Hotmelt Film (polyurethane)
Adhesive	Synthetic Resin
Flock	Rayon Viscose

APPLICATION INFORMATION

- Application to cotton, poly/cotton, polyester
- Washing fastness up to 104°F (40°C)
- Transfers to cloth 15-17 seconds
320-340°F (160-170 °C)
- Low / medium pressure

TRANSFER TAPE

EcoPrint requires RTape's specially formulated **HotMask** transfer tape to lift your printed graphic from the carrier and then heat apply using a standard heat press. Ask your supplier for **HotMask** to assist and ensure the highest quality transfer.



RTape Corporation
 6 Ingersoll Road
 South Plainfield, NJ 07080
 T 1-800-440-1250
 F 1-908-753-5014
 T 1-908-753-5570
 www.rtape.com
 sales@rtape.com



Manufacturing processes and related products are protected by existing patents: FR 97 12921; EUR 98 402 542.9; US 6.224.707; FR 98 12862; EUR 99 402 398.4; US 6.249.297; FR 04 08625; FR 05 05379; FR 05 05380. International extensions and new applications pending.